Hydraulic Power Unit 5

General Specifications

- Matched to BSL Hydraulic Winches 4 and 5
- Flow Max 220lpm
- Pressure Max 320Bar

Services

This self-contained hydraulic power unit (HPU), designed to be used alongside Hydraulic winch 4 and 5. Air cooled fan assisted. Adjustable flow and pressure.





Specifics

Item	Value
Shipping Weight (Tare)	~1000KG
Shipping Weight (Gross with oil)	2115KG
Shipping Dimensions (L,W,H)	1700 x 1450 x 2060mm
Tank Capacity	1200L
Power Supply	380-440VAC, 170-200A, 50/60Hz
Motor	75KW
Power Cable Length	30m
Hydraulic Hose Length	30m
Flow Set to	180LPM – MAX 220LPM
Pressure Set to	200Bar – MAX 320Bar
Hydraulic Fittings 1	ISO A Quick release, 1" BSP FEMALE C/STEEL
Hydraulic Fittings 2	ISO A Quick release, 1" BSP FEMALE C/STEEL

Benthic Solutions Limited, Unit A Greengates Way, Hoveton, Norwich, NR12 8ED, UK

☎ +44 (0) 1603 784726 ✉ enquiries@benthicsolutions.com 🌐 www.benthicsolutions.com